


GUANTE NITRILO JUBA - 113131 ECO-NIT

Guante sin costuras de poliéster recubierto de nitrilo estanco



NORMATIVA



GUANTES DE TRABAJO RECOMENDADOS PARA:

- Manipulación y ensamblaje de piezas pequeñas.
- Automoción.
- Construcción.
- Montaje ligero.

ESPECIALES

CARACTERÍSTICAS

- Buen agarre en entornos secos, húmedos y aceitados.
- Versión económica industrial.
- Disponible con bolsa individual para punto de venta (B113131)

Poliéster + Nitrilo eco-nit
código acabado color

Palma
113131recubiertaBlanco/Gris
nitrilo

	grueso	largo	talla	embalaje
XS -	22cm			
S -	23cm	XS/6	10	
M -	24cm	S/7	pares/paquete	
L -	25cm	M/8	120	
XL -	26cm	L/9	pares/caja	
		XL/10		

MÁS INFORMACIÓN

Materiales	Color	Grueso	Largo	Tallas	Embalaje
Nitrilo	Gris / Blanco	Galga 13	XS - 22 cm S - 23 cm M - 24 cm L - 25 cm XL - 26 cm XXL - 27 cm	6/XS 7/S 8/M 9/L 10/XL 11/XXL	10 pares/paquete 120 pares/caja


NORMATIVAS



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30